

**ELECTRICAL SPECIFICATIONS:**

- 1.) FREQUENCY RANGE: 698 - 2700 MHz
- 2.) IMPEDANCE: 50 OHMS
- 3.) INSERTION LOSS (MAX): 1.8 dB (ABOVE 12.04 dB SPLIT)
- 4.) AMPLITUDE BALANCE (MAX): 0.6 dB
- 5.) PHASE BALANCE (MAX): 10 DEGREES
- 6.) ISOLATION (MIN): 20 dB
- 7.) INPUT VSWR (MAX): 1.50 : 1
- 8.) OUTPUT VSWR (MAX): 1.20 : 1

**MECHANICAL SPECIFICATIONS:**


- 1.) CONNECTORS: SMA & TYPE-N FEMALE (JACK), 50 OHM
- 2.) CONNECTOR BODIES: BRASS, TRI-ALLOY PLATE
- 3.) CONNECTOR PINS: BE CU & PHOSPHOR BRONZE, GOLD PLATE
- 4.) INSULATORS: PTFE, VIRGIN ELECTRICAL GRADE
- 5.) HOUSING: ALUMINUM, CLEAR CHEM CONVERSION FILM, RoHS COMPLIANT (NO HEX CHROM)
- 6.) SOLDER: LEAD FREE, RoHS COMPLIANT
- 7.) OPERATING TEMP: -65°C TO +85°C
- 8.) WEIGHT: 1706 GRAMS

**RF INPUT POWER RATING (POWER DIVIDER SPLITTER):**

INTO MATCHED LOAD VSWR's	IN-PHASE	180° OUT-OF-PHASE
1.2 : 1	40 WATTS	40 WATTS
2.0 : 1	40 WATTS	40 WATTS
∞	20 WATTS	8 WATTS

**RF INPUT POWER RATING (POWER COMBINER):**

COHERENT SIGNALS (IN-PHASE)	16 X 2.5 WATTS
COHERENT SIGNALS (180° OUT-OF-PHASE)	16 X 0.5 WATTS
NON-COHERENT SIGNALS	16 X 1 WATT
OTHER CONDITIONS - CONSULT FACTORY	



**RoHS**

REV	DESCRIPTION	BY	DATE

TOLERANCES	
INCHES	MILLIMETERS
.00 = ±.01	.0 = ±.25
.000 = ±.004	.00 = ±.10
DRAWN: MJD	APPROVED: EMM
DATE: 01/24/08	DATE: 01/24/08

**STOCK**  
wireless components  
www.instockwireless.com

MODEL NO.	<b>PD2216</b>
TITLE	16 WAY POWER DIVIDER COMBINER, SMA & TYPE-N, 698-2700 MHz, 40W, 50 OHM, 0 DEGREE (IN-PHASE), RoHS