

ELECTRICAL SPECIFICATIONS:

- 1.) FREQUENCY RANGE: 698 - 2700 MHz
- 2.) IMPEDANCE: 50 OHMS
- 3.) INSERTION LOSS (MAX): 0.6 dB (ABOVE 4.77 dB SPLIT)
- 4.) AMPLITUDE BALANCE (MAX): 0.2 dB
- 5.) PHASE BALANCE (MAX): 3 DEGREES
- 6.) ISOLATION (MIN): 18 dB
- 7.) INPUT VSWR (MAX): 1.30 : 1
- 8.) OUTPUT VSWR (MAX): 1.25 : 1

MECHANICAL SPECIFICATIONS:


- 1.) CONNECTORS: QMA FEMALE (JACK), SOCKET CONTACT
- 2.) CONNECTOR BODY: BRASS, TRI-ALLOY PLATE
- 3.) CONNECTOR PIN: BERYLLIUM COPPER, GOLD PLATE
- 4.) INSULATOR: PTFE, VIRGIN ELECTRICAL GRADE
- 5.) HOUSING: ALUMINUM, CLEAR CHEM CONVERSION FILM, RoHS COMPLIANT (NO HEX CHROM)
- 6.) SOLDER: LEAD FREE, RoHS COMPLIANT
- 7.) OPERATING TEMP: -65°C TO +85°C
- 8.) WEIGHT: 294 GRAMS

RF INPUT POWER RATING (POWER DIVIDER SPLITTER):

| INTO MATCHED LOAD VSWR's | IN-PHASE | 180° OUT-OF-PHASE |
|--------------------------|----------|-------------------|
| 1.2 : 1 | 40 WATTS | 40 WATTS |
| 2.0 : 1 | 40 WATTS | 10 WATTS |
| ∞ | 20 WATTS | 1 WATT |

RF INPUT POWER RATING (POWER COMBINER):

| | |
|--------------------------------------|----------------|
| COHERENT SIGNALS (IN-PHASE) | 3 X 13.3 WATTS |
| COHERENT SIGNALS (180° OUT-OF-PHASE) | 3 X 0.33 WATTS |
| NON-COHERENT SIGNALS | 3 X 0.66 WATTS |
| OTHER CONDITIONS - CONSULT FACTORY | |



| REV | DESCRIPTION | BY | DATE |
|-----|-------------|----|------|
| | | | |

| TOLERANCES | |
|----------------|----------------|
| INCHES | MILLIMETERS |
| .00 = ±.01 | .0 = ±.25 |
| .000 = ±.004 | .00 = ±.10 |
| DRAWN: KMG | APPROVED: MJD |
| DATE: 03/02/18 | DATE: 03/02/18 |

INSTOCK
wireless components
www.instockwireless.com

| | |
|-----------|---|
| MODEL NO. | PD2730 |
| TITLE | 3 WAY POWER DIVIDER COMBINER, QMA FEMALE, 0.698 - 2.700 GHz, 40W, 50 OHM, 0° (IN-PHASE), RoHS |