

**ELECTRICAL SPECIFICATIONS:**

- 1.) FREQUENCY RANGE: 350 - 1000 MHz
- 2.) IMPEDANCE: 50 OHMS
- 3.) INSERTION LOSS (MAX): 1.4 dB (ABOVE 10.79 dB SPLIT)
- 4.) AMPLITUDE BALANCE (MAX): 0.4 dB
- 5.) PHASE BALANCE (MAX): 7 DEGREES
- 6.) ISOLATION (MIN): 18 dB
- 7.) INPUT VSWR (MAX): 1.45 : 1
- 8.) OUTPUT VSWR (MAX): 1.25 : 1

**MECHANICAL SPECIFICATIONS:**


- 1.) CONNECTORS: BNC FEMALE (JACK), 50 OHM
- 2.) CONNECTOR BODY: BRASS, TRI-ALLOY PLATE
- 3.) CONNECTOR PIN: BERYLLIUM COPPER, GOLD PLATE
- 4.) INSULATOR: PTFE, VIRGIN ELECTRICAL GRADE
- 5.) HOUSING: ALUMINUM, CLEAR CHEM CONVERSION FILM, RoHS COMPLIANT (NO HEX CHROM)
- 6.) SOLDER: LEAD FREE, RoHS COMPLIANT
- 7.) OPERATING TEMP: -65°C TO +85°C
- 8.) WEIGHT: 1477 GRAMS

**RF INPUT POWER RATING (POWER DIVIDER SPLITTER):**

INTO MATCHED LOAD VSWR's	IN-PHASE	180° OUT-OF-PHASE
1.2 : 1	30 WATTS	30 WATTS
2.0 : 1	30 WATTS	30 WATTS
∞	15 WATTS	3 WATTS

**RF INPUT POWER RATING (POWER COMBINER):**

COHERENT SIGNALS (IN-PHASE)	12 X 2.5 WATTS
COHERENT SIGNALS (180° OUT-OF-PHASE)	12 X 0.25 WATTS
NON-COHERENT SIGNALS	12 X 0.5 WATTS
OTHER CONDITIONS - CONSULT FACTORY	



**INSTOCK**  
wireless components

**PD2513**  
DIVIDER/COMBINER

instockwireless.com

**UHF/RF**  
350-1000 MHz

REV	DESCRIPTION	BY	DATE	TOLERANCES		MODEL NO.
				INCHES	MILLIMETERS	
				.00 = ±.01	.0 = ±.25	<b>PD2513</b>
				.000 = ±.004	.00 = ±.10	
				DRAWN: MJD	APPROVED: EMM	TITLE 12 WAY POWER DIVIDER COMBINER, BNC FEMALE, 350 - 1000 MHz, 30W, 50 OHM, 0 DEGREE (IN-PHASE), RoHS
				DATE: 03/13/12	DATE: 03/13/12	

**INSTOCK**  
wireless components  
www.instockwireless.com